Hazard Analysis and Fault Tree Analysis

Bill Vesely

NASA HQ

Use of a Fault Tree in Identifying Hazards

- When a fault tree is used to identify the hazards then it is often called a Master Logic Diagram (MLD)
- The top event is the undesired event that can result from the hazards
- The top event is resolved to initiating events that can result in the undesired event
- Each initiating event is developed into an accident scenario to assess the associated risk
- Each initiating event is also linked to the conditions enabling the initiating event

A Master Logic Diagram for the Space Shuttle for Loss of Crew and Vehicle (LOCV) Due to Fire

LOCV Due to Loss of Structural Integrity Caused by Fire/Explosion during Ascent

LOCV-Ascent-LS-FirExp

2
1

APU caused Fire/Explosion

SRB caused Fire/Explosion

MPS caused Fire/Explosion

OMS/RCS caused Fire/Explosion

FCP fuel leak

APU exhaust leak damage

APU fuel leak damage

RSRM failures causing element Fire/Explosion

SRB System failure causing STS element Fire/Explosion

Overpressurezation due to OMS failure

Overpressurization due to RCS failure

RSS destruct command of STS due to element failure

Foreign object damage

RSRM fails to maintain safe STS attitude/performance due to Thrust failure

Overpressurization due to MPS failure

ET Fire/Explosion

Fire/Explosion of STS during Separation

Structure breakup of RSRM resulting in Fire/Exp of STS vehicle

RSRM structural failure causing Fire/Explosion in other STS elements

MPS fuel leak

ET failure causing element Fire/Explosion

MPS H2 leak

MPS O2 leak

SSME Fire/Explosion

Orbiter failure causing element Fir/Explosion

Fire/Explosion of other STS elements

Structure failure of RSRM components

Orboter I/F leakage

**PRSD caused Fire/Explosion**

3

Constructing an Accident Scenario for Each Initiating Event

- The accident scenario defines additional enabling events (pivotal events) which are necessary for the initiating event to progress to the undesired final event
- The pivotal events in the accident scenario are resolved to basic causal events at which controls are applied
- The initiating event can also be resolved to more basic causal events where controls can be instituted

Approaches for Constructing the Accident Scenario

- ◈ Event Sequence Diagrams (ESDs) construct the accident scenario as a chain sequence

- ◈ Event Trees (ETs) construct the accident scenario as an event tree

- ◈ Fault Trees (FTs) construct the accident scenario as a fault tree

Illustration of a Basic Event Sequence Diagram

Initiating Event → Pivotal Event → Pivotal Event → Final Undesired Event

An Event Sequence Diagram (ESD) for a Hazard Analysis of Cracks Existing in the Turn-Around-Duct of the High Pressure Pump of the SSME

2nd Stage Impeller Blade
ESD ~ Pre-Existing Flaw

Pre-Existing Crack

PE 1
Missed Crack Inspection

PE 2
Critical Crack Size

PE 3
Critical Area

PE 4
Loss of Impeller Head Rise

PE 5
Loss of Turbine Power

PE 6
Turbine Overtemp

PE 7
Redline Failure

LOC/V

PE 8
Loss of Torque Carrying Capability

PE 9
Disk Over Speed, Burst, Case Penetration

PE 10
Fire/ Explosion

LOC/V

8

Event Sequence Diagram for External Leakage of Hydrazine in the APU

External Leakage of Hydrazine → Yes → Sufficient Hydrazine Release → Yes → Ignition Source Present → Yes → LOV/C

Random Failure Or Missed Defect

Sufficient Hydrazine Release → No → MS (Mission Success)

Ignition Source Present → No → MS (Mission Success)

Basic Event Tree Model

Initiating Event	Pivotal Event	Pivotal Event	Pivotal Event	

MS

MS

MS

No

Yes

Undesired Event

ET Weld Defect Event Tree

Make Weld	No critical defect in weld	Critical defect detected before proof	No critical defect in repaired weld	Critical defect in repaired weld detected before proof	Critical defect survives proof	Post proof NDE required?	Critical defect in weld detected during post proof NDE		
Weld	Good-Weld	Pre-Proof-NDE	Post-Repair-Defects	Post-Repair-NDE	Proof	Require-Post-Proof-NDE	Post-Proof-NDE	#	End-State Names

```
Make Weld
 ├─ No critical defect in weld ──────────────────────────────────── 1  Good weld
 └─ Critical defect in weld
     ├─ Repair weld
     │   ├─ Weld fixed ─────────────────────────────────────────── 2  Weld repair good
     │   └─ Critical defect still in weld
     │       ├─ Repair tank ───────────────────────────────────── 3  Repair weld
     │       └─ Critical defect still in weld
     │           ├─ Critical defect still in weld
     │           │   ├─ Repair tank ──────────────────────────── 4  Repair & reproof
     │           │   └─ Critical defect still in weld ─────────── 5  Flawed weld on
     │           └─ Repair tank ──────────────────────────────── 6  Repair & reproof
     └─ Weld unrepaired
         └─ Critical defect still in weld
             ├─ Another chance to find defect
             │   ├─ Repair tank ──────────────────────────────── 7  Repair & reproof
             │   └─ Critical defect still in weld ─────────────── 8  Flawed weld on
             └─ Critical defect still in weld ──────────────────── 9  Flawed weld on
                 Repair tank ────────────────────────────────── 10  Repair & reproof
```

PRA-Weld-Model - Event Tree Diagram for Weld

Weld Process Example

LOCV due to Fire From a Pre-existing Crack

Mass fragments generated

Fire occurs from mass fragments

Rubbing of Pump

Rubbing of pump generates mass fragments

Rotor shift due to crack

Rotor shift causes rubbing of pump

Crack missed by inspection

Crack causes rotor shift

Fault Tree for the Hazard of a Crack Causing a Fire and LOCV

12

SRB–TVC–APU–LF–HDZ–LK–CFL

Leak Initiating Event
SRB_TVC_APU_LF_LK_IE

Screening Misses Leak
SRB_TVC_APU_LF_LK_SC

Sufficient Quantity
SRB_TVC_APU_LF_LK_SQ

Ignition Source
SRB_TVC_APU_LF_LK_IG

Accident Scenarios Modeled in Fault Trees

SRB–TVC–APU–LF–HDZ–LK–RC

Leak Initiating Event
SRB_TVC_APU_LF_LK_IE

Leak Caught, Prob. Of Reoccurrence
SRB_TVC_APU_LF_LK_RC

Sufficient Quantity
SRB_TVC_APU_LF_LK_SQ

Ignition Source
SRB_TVC_APU_LF_LK_IG

13

A Fault Tree is Generally Not Recommended for Scenario Modeling

- An accident scenario generally involves a time sequence of events
- Accident scenario modeling is inductive and determines subsequent events and resulting consequences
- Accident scenarios are best modeled using ESDs or ETs
- A fault tree is a deductive model resolving an undesired event into primary causes
- FTs are best applied in resolving the events in an accident scenario to primary causal events

FTA Application in Resolving an Event to Basic Causal Events

- The top event of the FT is the initiating event or one of the enabling events in the accident scenario

- The FT is developed to basic causal events at which controls are applied

- The basic causal event description includes the relevant failure mode as done in standard FTA

- Primitive root causes of the basic causal event are not resolved unless controls are applied at this level

Use of a FT in Modeling System Failures in an Accident Scenario

- ◆ Certain of the enabling events (pivotal events) in the accident scenarios can in particular involve system failures

- ◆ A fault tree is then constructed for each system failure to resolve to component failures or basic causes

- ◆ The fault trees are then linked to the accident scenarios to evaluate the accident risks

Illustration of a Basic Event Sequence Diagram with a Linked Fault Tree

Reference

♦ **"Fault Tree Handbook with Aerospace Applications',
Version 1.1, NASA Publication, August 2002.**